






HMC Wire

HIGH GRADE STAINLESS STEEL RIGGING WIRE

HMC was initially used exclusively by leading sparmakers Seldén of Sweden. Because of the critical importance of quality in yacht rigging, top specialists demand exceptionally high standards in every component they use. The rigging wire is of course one of the most critical of all, hence their decision to specify only HMC.

Type	Size	Part No.	Mass approx kg/100m	Minimum breaking strain. kgf	Min. rec. sheave mm
1 x 19	3mm	HM-601-001	4.39	706	-
	4mm	HM-601-002	7.81	1260	-
	5mm	HM-601-003	12.20	1960	-
	6mm	HM-601-004	17.60	2820	-
	7mm	HM-601-005	23.90	3480	-
	8mm	HM-601-006	31.20	4550	-
	10mm	HM-601-008	48.80	7110	-
	12mm	HM-601-009	70.30	10200	-
7 x 19	3mm	HM-602-001	3.34	510	48mm
	4mm	HM-602-002	5.94	908	64mm
	5mm	HM-602-003	9.29	1420	80mm
	6mm	HM-602-004	13.40	2040	96mm
	7mm	HM-602-005	18.20	2785	112mm
1 x 19	4/6mm	HM-601-011	9.25	1260	-
	PVC Coated 5/8mm	HM-601-012	14.70	1960	-
	Guard Rail Wire				



On the world's oceans HMC has more than lived up to expectations. The remarkable voyage of the 40ft steel ketch Northern Light included some of the harshest conditions to be found on the planet. Despite severe storms, the searing heat of the Tropics, and a ferocious Antarctic winter, her HMC rigging performed faultlessly, for over 30,000 miles.