

# Hauling & Lifting Winches

## Goliath Winches



Recent design advances have resulted in greater strength and durability for the Goliath winch range. In co-operation with leading materials handling specialists, Goliath engineers have made changes which significantly lessen wear in key components, leading to reduced down-time for service or parts replacement.

The versatile automatic braking range now offers winches with a lifting capacity from 140kg to 1700kg. All are CE marked and the AF range have TUV Security accreditation, including stainless steel models.

05-50601



### Manual Winches

CODE	DESCRIPTION
05-50301	3N1 425kg Single Speed Winch
05-50501	5N1 575kg Single Speed Winch
05-50601	6N1 650kg Single Speed Winch
05-50701	7N1 750kg Single Speed Winch
05-50901	9N1 985kg Single Speed Winch
05-50907	9N1F 985kg Single Speed Winch c/w Hand Brake
05-51201	12N2 1200kg Two Speed Winch
05-51207	12N2F 1200kg Two Speed Winch c/w Hand Brake
05-51601	16N2 1600kg Two Speed Winch
05-51607	16N2F 1600kg Two Speed Winch c/w Hand Brake
05-52507	25N3F 2300kg Three Speed Winch c/w Hand Brake

Winches

	4AFM	4AF/4AFL	6AF/6AFL	8AF/8AFL	12AF/12AFL	30AF**
+Hauling power Kg	450	460	600	800	1300	3700
Lifting power Kg	170	190	240	300	500	1700
Dimensions mm	125x105x95	125x145x95	160x155x130	200x155x170	210x190x170	300x170x240
Weight Kg	2.6	2.6	3.6	5.5	7.3	13.7
Transmission ratio	1:2.57	1:2.57	1:3.5	1:4.85	1:9.71	1:21.8
Drum diameter mm	30	40	50	60	76	80
Handle length mm	160	160	200	200	250	290
Rec. wire size*	3mm x 8m	4mm x 10m	5mm x 13m	6mm x 16m	7mm x 10m	9mm x 20m

+ Loads are calculated on a 30 degree ramp (handle load is based on a power of 20 kg)

PART No.						
Standard AF Winch	G5-54423	G5-54422	G5-54613	G5-54817	G5-55123	G5-33001
Standard AFL Winch			G5-54601	G5-54818	G5-55121	
Stainless Steel Winch	G5-54418	G5-54419	G5-54612	G5-54816	G5-53119	

\* Drums suitable for webbing belt are available if required - please specify when placing orders

for further information call **01489 570797**