

# Rigging Screws

## HASELFORS

### Rigloc

This new series of chrome plated aluminium bronze rigging screws is the latest addition to our range. Aluminium bronze, like stainless steel, is very strong and highly resistant to corrosion. By making the body of the rigging screw in chrome plated aluminium bronze and the terminals in high grade marine stainless steel,

we have reduced the risk of the thread seizing up under heavy loads. A design feature which gives you a product that lasts even longer. These rigging screws have a new type of locking device, Rigloc.

#### Fork & Fork



Part No.	Thread	Length		Clevis pin diameter mm	Fork Width mm	Fork Height mm(H1)	Breaking point kN	Max. Working load kN
	UNF	min. mm	max. mm					
HF-90021	1/4	135	192	6.5	7	12.5	15	10.5
HF-90022	5/16	170	230	8	8	15	23	16.1
HF-90023	3/8	205	277	9.5	10	18	34	23.8
HF-90024	7/16	236	335	11	12	18	47	32.9
HF-90025	1/2	280	393	13	14	24	68	47.6
HF-90026	5/8	334	463	15.8	16	31	95	66.5
HF-90027-2	3/4	389	539	19	20	32	125	87.5
HF-90028-2	7/8	431	620	22	22	45	180	125

#### Fork & Stud



Part No.	Thread	Wire dia mm	Length		Clevis pin diameter mm	Fork Width mm	Fork Height mm(H1)	Breaking point kN	Max. Working load kN
	UNF	min. mm	max. mm						
HF-90113	1/4	3	182	239	6.5	7	12.5	15	10.5
HF-90114	1/4	4	187	244	6.5	7	12.5	15	10.5
HF-90115	5/16	4	210	270	8	8	15	23	16.1
HF-90116	5/16	5	230	290	8	8	15	23	16.1
HF-90118	3/8	5	262	329	9.5	10	18	34	23.8
HF-90120	3/8	6	269	336	9.5	10	18	34	23.8
HF-90122	7/16	6	300	399	11	12	18	47	32.9
HF-90123	7/16	7	308	407	11	12	18	47	32.9
HF-90125	1/2	7	333	446	13	14	24	68	47.6
HF-90126	1/2	8	344	457	13	14	24	68	47.6
HF-90128	5/8	8	388	517	15.8	16	31	95	66.5
HF-90129	5/8	10	405	534	15.8	16	31	95	66.5
HF-90130-2	3/4	10	460	610	19	20	32	125	87.5
HF-90131-2	3/4	12	495	645	19	20	32	125	87.5
HF-90132-2	7/8	12	555	744	22	22	45	180	125
HF-90133-2	7/8	14	570	759	22	22	45	180	125